
Lok-it! HTI 1000/PS

Lok-it! | Metal halide lamps

Product benefits

- Lamp and holder from a single source
- Rapid relamping with bayonet lock

Product features

- eXtreme Seal technology for discharge lamps



Product datasheet

Technical data


Electrical data

Nominal voltage	85.0 V
Lamp voltage	85 V
Nominal current	11.8 A
Lamp current	11.8 A
Nominal wattage	1000.00 W

Photometrical data

Nominal luminous flux	120000 lm
Color temperature	6000 K
Color rendering index Ra	92

Dimensions & weight



Diameter	27.0 mm
Length	125.0 mm
Light center length (LCL)	56.0 mm
Electrode gap cold	5.5 mm

Lifespan

Lifespan	750 h
----------	-------

Certificates & standards

EEI – Energy Label	B
--------------------	---

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321788368	Lok-it! HTI 1000/PS	Shipping carton box 1	305 mm x 82 mm x 115 mm	2.88 dm ³	204.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.