


## Product information:

---

The PNC2527 is a hybrid power/network cable which consists of 3x 2,5mm<sup>2</sup> power section and 2 x CAT 7 LAN cable. As more and more equipment is network-based this cable is perfectly suited to provide the necessary power and redundant data to these devices. The power and 2x LAN cable each have a separate jacket which makes it easy to split out the cables at the end.




## Certification:

---

## Properties:

---



## Usage:

---

RENTAL


## Physical Characteristics:

|                 |          |                      |          |   |
|-----------------|----------|----------------------|----------|---|
| Inner conductor | Power    | Insulation           | Material | PVC 3.7 mm (Ø)  |
|                 |          |                      | Colours  | Blue / Brown / Yellow & Green   |
| Inner jacket    | Material |                      |          | PVC 10 mm (Ø)   |
| Inner conductor | Data     | Insulation           | Material | FPE 1.55 mm (Ø)   |
|                 |          |                      | Colours  | Green / White & Green ; Blue / White & Blue ; Orange / White & Orange ; Brown / White & Brown |
| Inner jacket    | Material |                      |          | PVC 6.3 mm (Ø)  |
| Outer jacket    | Material |                      |          | PVC 20.9 mm (Ø)   |
|                 |          |                      | Colours  | Black   |
| Inner conductor | Power    | Material             |          | BC 48 x 0.25 mm (Ø) (OFC)   |
|                 | Data     | Material             |          | BC 1 x 0.13 mm (Ø) (OFC)  |
|                 | Power    | Section              |          | 2.5 mm <sup>2</sup>   |
|                 | Data     | Section              |          | 0.13 mm <sup>2</sup>  |
|                 | Power    | American Wire Gauge  |          | 14 AWG  |
|                 | Data     | American Wire Gauge  |          | 26 AWG  |
|                 | Power    | Number of conductors |          | 3   |
|                 | Data     | Number of conductors |          | 8 (4 pairs)   |

## Electrical Characteristics:

|                        |               |               |
|------------------------|---------------|---------------|
| Max. operation voltage | Power         | 500 V         |
| Max. conductor         | DC resistance | 7.98 (Ω / Km) |
|                        |               | 148 (Ω / Km)  |

## Cross sections:



## Variants:

- PNC2527/1 - 100 meter
- PNC2527/3 - 300 meter